



Control4® 7" In-Wall Touch Screen with Camera

Control4® 7" In-Wall Touch Screen with Camera
C4-TW7C0-BL
C4-TW7C0-WH

The Control4® 7" In-Wall Touch Screen with Camera delivers always-on, dedicated system control in an elegant, low profile form factor that can be easily mounted on the wall. The 7" In-Wall Touch Screen with Camera features full-motion video intercom and the fidelity of wideband audio intercom for crystal-clear communications and control throughout a home or business. Intercom is optional and may be activated with the purchase of an Intercom License (C4-Intercom-E).

- Sleek look and feel with edge-to-edge capacitive glass and low-profile mount make this a visually stunning, total control solution.
- Full-color, capacitive LCD touch screen control.
- Four customizable buttons allow you to set your favorite scenes with one touch.
- Compatible with virtually any new or existing home with options in power (AC or Power over Ethernet) and network connectivity (Ethernet or WiFi).
- Integrated camera with full-motion video for high-quality video communications with Door Station with Camera and 7" In-Wall Touch Screen with Camera.
- Integrated speakers and dual microphones with beam forming and G.722 wideband audio for uncompromised high-fidelity sound.
- Video intercom integration with the following door stations and in-wall touch screens: Door Station (C4-DSC-EN-XX); 7" Portable Touch Screen with Camera (C4-TSMC7-EN-XX).
- Audio intercom integration with the following in-wall touch screens: 5" In-Wall Touch Screen (C4-TSWMC5-EG-XX); 7" In-Wall Touch Screen (C4-TSWMC7-EG-XX).
- Available in white or black.

Control4™

Control4® 7" In-Wall Touch Screen with Camera

Model Numbers	C4-TW7C0-BL C4-TW7C0-WH
Display	
Camera	640 x 480 VGA 30 fps Min. lumenation: 5 Lux Viewing angle: 60 degrees
Display dimensions	7-inch TFT 800 x 480 pixels
Touch screen	Capacitive touch
Programmable buttons	4
Intercom	
Intercom	Full duplex video (h.264)/audio (G.722 wideband audio) intercom
Microphone	Dual microphones Beam forming
Network	
WiFi	IEEE 802.11 n/g/b RF frequency: 2.4 GHz Antenna: Internal Encryption: 64/128 WEP, TKIP/AES Authentication: WEP, WPA, WPA2
Ethernet	10/100 BaseT Ethernet RJ-45
Power	
Power supply	PoE (IEEE802.3af) 13 W peak AC 100V - 240V, 50-60 Hz
Mounting Options	
Dimensions (H x W x D)	4.88" x 7.2" x .60"
Mounting	In-Wall
Weight	1.15 lbs
Shipping Weight	1.8 lbs
Other	
Reset	Reset - Magnet Restore switch on back
Operation temperature	32° F - 104° F (0° C - 40° C) 95% non-condensing
Storage temperature	-49° F - 167° F (-45° to 75° C)
Accessories	
Intercom License	C4-Intercom-E
New Construction In-Wall Touch Screen Back Box, Plastic	C4-NWB57C-P
New Construction In-Wall Touch Screen Back Box, Metal	C4-NWB57C-M
Retrofit In-Wall Touch Screen Back Box, Plastic	C4-RWB57C-P
Retrofit In-Wall Touch Screen Back Box, Metal	C4-RWB57C-M

Also available are the Control4® 5" and 7" In-Wall Touch Screens (Audio Intercom-capable only) and 7" Portable Touch Screen with Camera (Audio and Video Intercom-capable). For a complete list of Intercom compatibilities, please refer to the Intercom License datasheet.

