

# CONTROL4 CA-1

## AUTOMATION CONTROLLER



## CONTROL4® CA-1

### C4-CA1

The Control4® CA-1 Automation Controller is the perfect entry point into Control4 automation built around security, comfort, and convenience solutions. It has built-in control for IP, ZigBee®, and serial devices, plus an internal slot for a Z-Wave Plus™ module (sold separately). It is designed for homeowners, builders, MDUs, and hotels that want smart experiences that include smart lighting, thermostats, door locks, cameras, sensors, shades, and more.

The CA-1 is the foundation that makes smart products work together to deliver rich, orchestrated automation—the smart home experience homeowners truly want.

- The simplest way to experience the Control4 Smart Home
- Orchestrated automation for door locks, shades, cameras, sensors, and lighting
- Built on Control4's proven OS and ecosystem
- Built-in connectivity for IP, ZigBee, and serial devices
- Expansion slot for optional Z-Wave module
- Perfect for broad-scale deployments
- Can be powered by PoE—making it an ideal tool to expand ZigBee in larger Control4 installations

# CONTROL4® CA-1 AUTOMATION CONTROLLER

## Specifications

Model number | C4-CA1

### Connections

Network	Ethernet—10/100BaseT compatible (required for controller setup), PoE supported
Wireless	Wireless N (2.4 GHz, 802.11n/g/b)
Wireless security	WPA/WPA2
Wireless antenna	External reverse SMA connector
ZigBee Pro	802.15.4
ZigBee antenna	External reverse SMA connector
USB port	2 USB 2.0 ports, 500mA
Serial out	1 serial out RJ45 port (RS-232)
Z-Wave	Integrated expansion slot accepts Control4 Z-Wave modules (sold separately)
Z-Wave modules	<a href="#">C4-ZWE</a> , <a href="#">C4-ZWH</a> , <a href="#">C4-ZWU</a> (sold separately)

### Power

Power requirements	5VDC 3A, external power supply included
Power supply	AC power supply accepts 100-240V ~ 50-60 Hz (0.5A)
PoE	802.3af (<13W)
Power consumption	Max 15W (51 BTU/hr)

### Miscellaneous

Operating temperature	32° - 104°F (0° - 40°C)
Storage temperature	4° - 158°F (-20° - 70°C)
Dimensions (H × W × D)	5.5 × 5.5 × 1.25" (14 × 14 × 3.8 cm)
Weight	0.65 lb (0.3 kg)
Shipping weight	1.5 lb (0.68 kg)

## More info

For more information on the CA-1 controller, visit [ctrl4.co/ca1](http://ctrl4.co/ca1)



For product photos, documentation and installation instructions, visit [ctrl4.co/controllers](http://ctrl4.co/controllers)



## Dimensions

