

# Control4® DS2 Door Station



## Control4 DS2 Door Station (C4-DS2FM, C4-DS2FMKP, C4-DS2SM, C4-DS2SMKP)

The Control4 DS2 Door Station delivers an amazing audio and HD video intercom experience, enabling customers to monitor and communicate with the front door or their security gate. Combined with Control4 touch screens, customers enjoy greater convenience and peace of mind throughout the home.

- Available in flush-mount and surface-mount options
- Optional integrated keypad is ideal for customers with gates or for those who want to add more security at their doors
- Fast connection speed
- Camera can be viewed outside of an intercom call
- Improved low-light performance
- Motion detection
- Camera snapshots can be emailed to a customer's mobile device
- Dealer-configurable doorbell sounds

## Control4 DS2 Door Station

|                        |  |
|------------------------|--|
| Model number           | C4-DS2FM, C4-DS2FMKP, C4-DS2SM, C4-DS2SMKP                                     |
| Video                  |  |
| Camera resolution      | 1280 × 960 (W×H)   |
| Camera view angle      | 120° × 90° × 145° (W×H×diagonal)   |
| Camera IR night vision | Yes  |
| Video stream codecs    | H.263+, H.263, H.264, MJPEG, MPEG-4  |
| Audio                  |  |
| Microphone             | Yes (integrated)   |
| Speaker                | 2W   |
| Acoustic pressure      | 78dB (1 kHz @ 1 meter distance)  |
| Audio stream codecs    | G.711, G.729   |
| Interface              |  |
| Power                  | PoE 802.3af (Class 0 - 12.95W)   |
| LAN                    | 10/100Base-TX with Auto-MDIX, RJ-45  |
| Relay outputs          | NC/NO contacts, max 30V/1A AC/DC   |
| Active output          | 8V-12VDC/400mA   |
| Dimensions             |  |
| Surface mount          | 4.21 × 9.21 × 1.10 in (107 × 234 × 28 mm) (W×H×thickness protruding from wall) |
| Flush mount            | 5.12 × 10.12 × 0.20 in (130 × 257 × 5 mm) (W×H×thickness protruding from wall) |
| Mechanical             |  |
| Operating temperature  | -40°F - 140°F (-40°C - 60°C)   |
| Storage temperature    | -40°F - 158°F (-40°C - 70°C)   |
| Relative humidity      | 10% - 95% (non-condensing)   |
| Protection level       | IP 54  |
| Accessories            |  |
| C4-DS2PLATE-BL         | Black cover plate  |