HALO TOUCH REMOTE



CONTROL4® HALO TOUCH REMOTE

C4-HALO-TS-BL | C4-HALO-TS-AS

Halo Touch is the new premium universal smart remote by Control4. The handheld device includes a host of user-driven features, such as a 3.2" color touch-interface with a complement of backlit buttons, voice control, extended battery life, WiFi 2.4 and 5GHz support, and a redesigned UI with new interaction options. Halo Touch also includes end-user install capabilities, and OvrC* integration that reports battery life and Wi-Fi connectivity data. With a generational leap in functionality and a refined design, Halo will redefine the user experience.



CONTROL4® HALO TOUCH REMOTE

FEATURES	DESCRIPTION
Model SKU Colors Housing	C4-HALO-TS-BL C4-HALO-TS-AS Black Silver Anodized Aluminum
Display	 Full Color Touchscreen LCD Resolution: 480 x 3(RGB) x 800 81mm (3.2 inches) diagonal 291 ppi 16.7 million colors Anti-glare
Ports and Interfaces	 WiFi (802.11 a/b/g/n/ac, SDIO, Main and Diversity antenna outputs) Accelerometer Near Field Microphone Speaker Ambient Light Sensor Charging Connector
WiFi Frequency of Operation	Frequency for 2.4GHz WLAN • b/g/n(HT20) - 2412MHz - 2462MHZ
	Frequency for 5GHz WLAN • W52 11a/n/ac ((V)HT20/40/80) - 5180MHz - 5240MHz • W53 11a/n/ac ((V)HT20/40/80) - 5260MHz - 5320MHz • W56 11a/n/ac ((V)HT20/40/80) - 5500MHz - 5725MHz • W58 11a/n/ac ((V)HT20/40/80) - 5745MHz - 5825MHz
	USA & Canada frequencies and max power levels • 2412 - 2462 MHz 0.193 W • 5180 - 5240 MHz 0.023 W • 5260 - 5320 MHz 0.024 W • 5550 - 5720 MHz 0.024 W • 5745 - 5825 MHz 0.016 W
	Europe, UK, Australia & New Zealand frequencies and max power levels • 2412 - 2462 MHz 0.061W • 5180 - 5240 MHz 0.028W • 5260 - 5320 MHz 0.027W • 5550 - 5720 MHz 0.027W • 5745 - 5825 MHz 0.022W
System	 Arm Cortex A7 single core @ 720MHz Cortex-M4 coprocessor Ultra Low Power Consumption Platform

• Intelligent Power Management



CONTROL4® HALO TOUCH REMOTE

FEATURES	DESCRIPTION
System Requirements	• OS 3.3.2+ • WiFi 2.4GHz or 5GHz
Power	 1900mAH Li-ion battery External 10W charger (included) 193.6mm (7.62in) x 51.5mm (2.03in) x 19mm (.75in)
Dimensions (H x W x D)	• 165g
Weight	
Included in the Box	RemoteDocking StationUSB-C Power SupplyCountry specific power plugQuick Start Documentation
Environmental	 Operating Temp: 0° to 35° C (32° to 95° F) Storage Temp: -20° to 45° C (-4° to 113° F) Relative Humidity: 20-90% non-condensing Avoid direct sunlight
Docking Station	
Dimensions (H x D)	• 18.0mm (.71in) x 78.00mm (3.07in)
Weight	• 294g
Ports	• USB-C

