

DALI-GATEWAY

BASIC, 1-FOLD, MDRC



General information

SKU	C4-KNX-DALI
Catalog description	DALI-Gateway, Basic, 1-fold, MDRC
Long description	For controlling DALI devices via the KNX bus. One DALI output for up to 64 DALI secondary products. DALI power supply is integrated. Control and status feedback are carried out via KNX per DALI slave (64), with lighting groups (16), together in broadcast or per scenes (16). Extensive fault and error messages are available with a self-contained emergency converter (64), according to EN 62386-202 is supported. Various emergency tests (e.g. function and duration tests) can be triggered via KNX and emergency converter. Feedback is sent. Slave, staircase, force, block, and scene functions are integrated. DALI telegram rate can change. For diagnostic use and individual change of the DALI address or group assignment, a separate Software-Tool is available.
Number of batteries	0

Dimensions

Product (H × W × D)	90 × 72 × 64 mm
Product net weight	0.133 kg

Package

Package level 1 units	1 piece
Package (H × W × D)	65 × 92 × 77 mm
Package level 1 gross weight	0.172 kg

Additional information

Communication interface	DALI interface
Degree of protection	IP20
Input voltage (U _{in})	85 ... 264V AC
Mounting type	DIN-rail adapter
Number of LEDs	1
Power loss	2W
Product main type	DALI Gateways and Light Controllers
Product type	KNX Lighting Device
Protocol type	DALI

MOST RECENT VERSION



ctrl4.co/knx-dali-ds