

# Control4® T3-7 7" Tabletop Touch Screen



## Control4 T3-7 7" Tabletop Touch Screen (C4-TT7-BL, C4-TT7-WH)

The Control4® T3 Series Tabletop Touch Screen delivers always-on, dedicated, and mobile control over all the technology in your home or business. Featuring a gorgeous new tablet design and stunning high-resolution graphics, this portable screen looks beautiful whether on a kitchen countertop or in the theater on your lap. This model includes HD video intercom and crystal-clear audio intercom for convenient communications from room to room or with visitors at the door.

- Available in a 7" model, the T3 Series Portable Touch Screen provides dedicated, elegant, and mobile control of your home.
- HD camera, combined with speakers and microphone, provides the best video intercom experience yet.
- Crisp picture with two and a half times the resolution of previous models.
- Extremely fast and responsive—up to 16 times faster than our previous touch screens.
- Easily configured as a true portable or as a tethered tabletop for flexible installation.
- Wired and wireless connections through Wireless-N and 10/100 Ethernet.
- Flexible power options with AC power supply adapter, Power over Ethernet (PoE), or internal battery.
- Video intercom integration with the following door stations and touch screens: Door Station (C4-DSC-EN), T3 Series In-Wall Touch Screens (C4-WALL7, C4-WALL10), and legacy touch screens (C4-TW7CO, C4-TSMC7).
- Audio intercom integration with the door station and the following touch screens: T3 Series In-Wall Touch Screens (C4-WALL7, C4-WALL10) and legacy touch screens (C4-TW7CO, C4-TSMC7, C4-TSWMC5, C4-TSWMC7).
- Available in gloss white or black.

# Control4® T3-7 7" Tabletop Touch Screen

Model numbers	C4-TT7-BL, C4-TT7-WH
Features	
Screen	Resolution: 1280 × 800 Capacitive touch Camera: 720p
Network	Ethernet or WiFi (802.11 g/n [2.4 GHz]) Notes: (1) 802.11b is not supported for Video Intercom. (2) Wireless-N is recommended for Video Intercom. The more devices that Video Intercom is broadcast to, the more response time and images are degraded.
Battery	3100 mAh Li-ion
Power supply	PoE (IEEE802.3af) 100VAC ~ 240VAC, 50-60 Hz International power supply adapters included
Dock connections	<ul style="list-style-type: none"><li>Ethernet</li><li>PoE</li><li>DC power</li></ul>
Mounting	Tabletop or portable
Environmental	
Operating temperature	32 - 104°F (0° - 40°C)
Storage temperature	32 - 104°F (0° - 40°C)
Dimensions (W × H × D)	Touch screen: 7.0" × 5.1" × 0.75" (178 × 130 × 19 mm) Dock: 4.2" × 2.3" × 3.1" (106 × 57 × 78 mm)
Weight	Touch screen: 0.7 lbs. (0.32 kg) Dock: 0.8 lbs (0.36 kg)

## Planning the installation

- Make sure the dock can be located near a power outlet and a strong WiFi signal.
- For the most reliable connection, we recommend running Ethernet to the dock.
- Make sure the touch screen's WiFi or Ethernet connection is on the same network as your controller and that the signal is strong.
- Communication agent is required for intercom use.
- Charge the touch screen for at least six hours before use.

## For more product information

Visit [ctrl4.co/t3series](http://ctrl4.co/t3series)

