MINI LCR

IN-CEILING, IN-ROOM, IN-WALL



MINI LCR

IN-CEILING, IN-ROOM, IN-WALL

With uncompromising sound, the Triad Mini LCR's compact design and flexible installation options allow easy placement in bedrooms, offices, family rooms, and other modest media settings. Equipped with compact 4" drivers, the Mini LCR can meet the needs of smaller rooms, while delivering delicate sound and realistic playback.

In an industry of generic, mass-produced products, Triad combines craftsmanship and customization in every order. Handcrafted in the US using the finest materials and components, Triad's fully engineered, sealed, and internally braced MDF enclosures deliver intricate acoustics and effortless playback, actualizing the artist's intent.

Complete the full surround sound experience by pairing with Triad Surrounds, Satellites, and Subs. Distinguished by its custom paint matching and veneer finishes, Triad speakers achieve unobtrusive elegance while retaining the integrity of sound.

Practicality and price don't diminish the performance of Triad's Mini LCR, ensuring expectations are exceeded.

FEATURES

- Compact design
- · AcoustiPerf metal grill
- Fully engineered, premium MDF enclosure
- · Acoustic suspension, two-way design
- · Complimentary paint matching available

IN-CEILING

- 45-degree angled baffle
- · Fits between ceiling joists
- Standard grill finish is white paint

IN-ROOM

- 3/8" sixteen-threaded mounting insert
- Hardwood veneer finishes available (standard finish is black paint)

IN-WALL

· Standard grill finish is white paint



MINI LCR IN-CEILING, IN-ROOM, IN-WALL

SPECIFICATIONS


MATERIALS	IN-CEILING/8	IN-ROOM	IN-WALL/4
Tweeter count	1	1	1
Tweeter size	1" (25 mm)	1" (25 mm)	1" (25 mm)
Tweeter type	Fabric dome	Fabric dome	Fabric dome
Woofer count	2	2	2
Woofer size	4" (11 cm)	4" (11 cm)	4" (11 cm)
Woofer type	Paper/fiber blend	Paper/fiber blend	Paper/fiber blend

PERFORMANCE	IN-CEILING/8	IN-ROOM	IN-WALL/4
Recommended amplifier power	25 - 125W	25 - 150W	25 - 125W
Impedance	8 ohm	4 ohm	8 ohm
Sensitivity (dB @ 2.83V, 1 m)	86 dB	87.5 dB	86 dB
Frequency response (+/- 3 dB)	88 Hz - 20 kHz	100 Hz - 20 kHz	88 Hz - 20 kHz
DIMENSIONS	IN-CEILING/8	IN-ROOM	IN-WALL/4
Cabinet specifications (L \times W \times D)	10 ³ / ₄ × 10 ³ / ₄ × 7 ¹ / ₂ " (27.3 × 27.3 × 19.1 cm)	$12^{1/2} \times 5^{5/8} \times 5^{15/16}$ " (31.7 × 14.3 × 15.1 cm)	$13 \frac{1}{2} \times 7 \frac{3}{16} \times 3 \frac{15}{16}$ " (34.3 × 18.3 × 9.9 cm)

Cabinet specifications (L × W × D)	$(27.3 \times 27.3 \times 19.1 \text{ cn})$
Hole cutout (L × W)	10 ⁷ / ₈ × 10 ⁷ / ₈ " (27.6 × 27.6 cm)
Frameless grill dimensions (L × W)	12 ¹ / ₄ × 12 ¹ / ₄ " (31 × 31 cm)
NCB size	S
Product weight (each)	13.2 lb (6 kg)
Shipping weight (each)	18 lb (8.2 kg)

PRODUCT NUMBERS	IN-CEILING/8
Shipping weight (each)	18 lb (8.2 kg)
Product weight (each)	
NCB size	S

$(31.7 \times 14.3 \times 15.1 \text{ cm})$ 8.5 lb (3.8 kg) 11 lb (5 kg) **IN-ROOM**







Painted finish 51606-1000-4 Veneer finish

21006-4000-4 21006-6000-4 41406-1000-4

DIMENSIONS




IN-CEILING



IN-ROOM





IN-WALL

