

SILVER MONITOR

IN-ROOM, IN-WALL, IN-CEILING



SILVER MONITOR

IN-ROOM, IN-WALL, IN-CEILING

Triad's Silver Monitor speakers captivate listeners with audiophile sound, immersing high-end media rooms with strikingly authentic audio reproduction. With proprietary enclosure technology and Scan-Speak Revelator® drivers—acclaimed as some of the finest performers in the business—these high-sensitivity, high-power speakers are well-suited for venues with critical two-channel listening, and multiple designs offer elegant, flexible solutions for speaker placement.

Each speaker can be used as a full-range monitor, a high-end component in a surround system, or with any of the Triad In-Room or In-Wall Subs. In each case, it delivers dynamic audio with stunning clarity.

Triad's Silver Monitors offer a professional-grade audiophile experience, achieving unobtrusive elegance while retaining the integrity of sound. The Silver Monitor is the envy of the high-end speaker industry, its superior components and design enhancing your music with authentic, intricate audio reproduction.

FEATURES

- Compact design
- Fully engineered, premium MDF enclosure
- Acoustic suspension, two-way design
- Braced enclosure keeps sound from bleeding into adjacent rooms
- Custom paint matching available

IN-ROOM

- Acoustic cloth grill
- Veneer finishes available

IN-WALL

- AcoustiPerf frameless metal grill

IN-CEILING

- 45 degree baffle angle
- AcoustiPerf frameless metal grill

SILVER MONITOR IN-ROOM, IN-WALL, IN-CEILING

SPECIFICATIONS

	MATERIALS	IN-ROOM	IN-WALL/4	IN-WALL/6	IN-CEILING/6
Tweeter size		(1) 1" (25 mm)	(1) 1" (25 mm)	(1) 1" (25 mm)	(1) 1" (25 mm)
Tweeter type		Fabric dome	Fabric dome	Fabric dome	Fabric dome
Woofer size		(2) 5 1/4" (14 cm)	(2) 5 1/4" (14 cm)	(2) 5 1/4" (14 cm)	(2) 5 1/4" (14 cm)
Woofer type		Paper/fiber blend	Paper/fiber blend	Paper/fiber blend	Paper/fiber blend
	PERFORMANCE	IN-ROOM	IN-WALL/4	IN-WALL/6	IN-CEILING/6
Recommended amplifier power		50 - 200W	50 - 200W	50 - 200W	50 - 200W
Impedance		4 ohms	4 ohms	4 ohms	4 ohms
Sensitivity (dB @ 2.83V, 1 m)		92.5 dB	92.5 dB	92.5 dB	91 dB
Frequency response (+/- 3 dB)		70 Hz - 20 kHz	70 Hz - 20 kHz	70 Hz - 20 kHz	70 Hz - 20 kHz
	DIMENSIONS	IN-ROOM	IN-WALL/4	IN-WALL/6	IN-CEILING/6
Cabinet specifications (L x W x D)		16 1/8 x 7 5/16 x 8 9/16" (41 x 18.6 x 21.8 cm)	19 x 10 3/4 x 3 15/16" (48.3 x 27.3 x 9.9 cm)	19 x 8 3/16 x 5 1/4" (48.3 x 20.8 x 13.4 cm)	19 x 10 3/4 x 5 15/16" (48.3 x 27.3 x 15 cm)
Hole cutout (L x W)		-	19 1/8 x 10 7/8" (48.6 x 27.6 cm)	19 1/8 x 8 3/16" (48.6 x 21.1 cm)	19 1/8 x 10 7/8" (48.6 x 27.6 cm)
Frameless grill dimensions (L x W)		-	20 5/16 x 12 1/16" (51.6 x 30.6 cm)	20 5/16 x 9 1/2" (51.6 x 24.1 cm)	20 5/16 x 12 1/16" (51.6 x 30.6 cm)
NCB size		-	C	K	C
Product weight (ea.)		28 lb (12.7 kg)	16.5 lb (7.5 kg)	10.2 lb (5 kg)	20 lb (9 kg)
Shipping weight (ea.)		34 lb (15.4 kg)	25 lb (11.3 kg)	16 lb (7.2 kg)	26 lb (11.8 kg)
	PRODUCT NUMBERS	IN-ROOM	IN-WALL/4	IN-WALL/6	IN-CEILING/6
Painted finish		25005-4000-1	45405-1000-2	45505-1000-2	55505-1000-2
Veneer finish		25005-6000-1	-	-	-
Pedestal (6")		25028-4000-1	-	-	-



DIMENSIONS

